



Firemaster® Omega

DESCRIPTION

An in-seam glove offering a wealth of design features. Incorporating advanced materials but ensuring that it is user friendly and exceptionally wearable to carry out all routine rescue operations.

FEATURES AND ADVANTAGES

Amara synthetic leather palm providing great levels of grip and comfort
Multiple Armotex palm patches to provide tough anti-cutting and anti-abrasion protection
4 way stretch fabric in red on back of hand for fit and comfort
Articulated padded knuckle pads to enhance the durability and protect the hand and knuckle against bumps and bruises
Reinforced fingertips greatly weaken the impact of pinches
Curved fingers for added dexterity and reduced hand fatigue
Wristlet cuff providing protection from ingress of debris
Fully lined with cut and sew Kevlar glass-fibre lining providing the user with full hand protection from cuts.

TECHNICAL SPECIFICATIONS

PALM: Amara

PATCHES: Armotex

BACK: 4-way stretch fabric

CUFF: Nylon

LINING: Kevlar blend

THREAD: Kevlar

SIZE AVAILABILITY

2XS/6, XS/7, S/8, M/9, L/10, XL/11, 2XL/12, 3XL/13

+ Bespoke

INDUSTRY APPLICATIONS

Fire & Rescue Services, Oil & Gas exploration, Lumbering, Mining, Automotive, Construction, Rigging, Heavy duty industry,



- Certified to EN388:2003, Gloves offering protection from Mechanical Risks.
- Multi layered palm area to protect against a multitude of hazards
- Dexterous enough to perform all tasks during wear
- Secure cuff area preventing ingress of debris and detritus
- Machine washable
- Over 165 years of glove manufacturing heritage
- Sizes : 8 standard sizes plus bespoke upon request

Firemaster[®] Omega

PROPERTY	LEVEL	METHOD	PROPERTY	LEVEL	METHOD
Abrasion Resistance	4	EN388	Tear Resistance	4	EN388
Blade/Cut Resistance	5	EN388	Puncture Resistance	3	EN388

GLOVE CARE AND MAINTENANCE

Gloves that are deemed non-repairable are to be disposed of when damaged. Gloves do not require the use of specialist solvent-based products for cleaning or maintenance and these should not be used under any circumstances. The design and materials used ensure that the user can maintain the gloves in hygienic condition.

For best results follow this procedure:

- Machine wash at 40 degrees centigrade
- Hang to dry away from direct sunlight or heat.
- Wash gloves before they become too soiled.
- Gloves may be washed with articles of a similar colour provided the above instructions are followed.
- Gloves may be wash up to 5 times without impacting performance levels indicated



Southcombe Brothers Ltd
Stoke-sub-Hamdon
Somerset TA14 6QD
UK
P: +44 (0) 1935 823567
F: +44 (0) 1935 822918
E: sales@southcombe.com
www.southcombe.com