



## Firemaster Vortex

Technical Rescue Glove, Style No: SB02749A

### DESCRIPTION and USE

A full inseam glove with pre-curved fingers, used for a multitude of tasks wherever hazardous objects pose a risk. The glove has been designed to offer the wearer a high degree of protection against mechanical risks including abrasions, cuts, tears, punctures and impact as well as some contact heat protection up to 250°C. It also contains a moisture vapour permeable (MVP) insert between the outer and lining providing a breathable barrier to liquids and blood borne pathogens. It provides the highest levels of dexterity so users can perform extrications and technical rescues without having to remove their gloves. The glove is manufactured in accordance with EN420 for fit and dexterity and EN388 for mechanical risks. It is certified to level 2 for contact heat under EN407.

### FEATURES AND ADVANTAGES

Knitted technical fabric on the palm provides outstanding levels of cut protection and when paired with the synthetic leather palm patches, end users can enjoy great levels of grip in dry and wet conditions.

Oil and water repellant 4 way stretch fabric in high-vis orange on the back of hand offers excellent levels of fit and comfort while at the same time providing breathability for the working hand.

Thermal plastic rubber (TPR) patches across the back of the hand, fingers and thumb with in built articulations protect the hand and knuckle against impacts, bumps and bruises.

Neoprene style fabric cuff provides all round protection from the ingress of debris and an excellent interface with most fire and rescue tunic cuffs.

Fully lined with brushed fleece lining and with a Moisture Vapor Permeable (MVP) insert ensuring users hands stay dry and comfortable.

### MATERIALS

- Palm: Knitted material, 70% polyethylene, 17% polyester, 13% glass-fibre, 446 grams per sq metre +/- 25 grams
- Patches: Synthetic coated fabric, 30% nitrile, 35% PU, 35% nylon, 0.6-0.8 mm
- Back: Oil & water repellent 4 way stretch fabric, 100% polyester, 254 grams per sq metre +/- 15 grams
- Cuff: 2 mm Hyprene neoprene style material, 91% polyester, 9% spandex, 380 grams per sq metre +/- 20 grams
- Lining: Brushed 100% polyester fleece
- Membrane: Moisture Vapor Permeable (MVP) insert
- Thread: Aramid yarn



- Certified to EN388: 2016 Gloves offering Protection from Mechanical Risks with maximum scores
- Certified to level 2 for contact heat under EN407: 2004
- TPR Patches across back of hand fingers and thumb
- Impact Protection
- Moisture Vapor Permeable insert
- 170 years of glove manufacturing experience
- XXS to XXL standard sizes + bespoke upon request

# Firemaster Vortex

## TEST RESULTS

PROPERTY	LEVEL	METHOD	PROPERTY	LEVEL	METHOD
Abrasion Resistance	4	EN388	Tear Resistance	4	EN388
Blade/Cut Resistance	X	EN388	Puncture Resistance	4	EN388
Straight Blade Cut (TDM) resistance	F	EN388	Impact	Pass	EN388
Dexterity	Level 4	EN420	Contact Heat	Level 2	EN407

## GLOVE CARE AND MAINTENANCE

Gloves that are deemed non-repairable are to be disposed of when damaged. Gloves do not require the use of specialist solvent-based products for cleaning or maintenance and these should not be used under any circumstances. The design and materials used ensure that the user can maintain the gloves in hygienic condition.

For best results follow this procedure:

- Machine wash at 40°C
- Use liquid detergent
- Hang with fingers uppermost to allow lining to drain
- Dry away from direct sunlight or heat.
- Wash gloves before they become too soiled
- Gloves may be washed with articles of a similar colour provided the above instructions are followed.
- Gloves may be wash up to 5 times without impacting performance levels indicated



Southcombe Brothers Ltd  
Stoke-sub-Hamdon  
Somerset TA14 6QD, UK  
P: +44 (0) 1935 823567  
E: sales@southcombe.com  
www.southcombe.com

# FIREMASTER®