Slash Resistant Uniform Glove

DESCRIPTION and USE

The ultimate in hand protection for officers on the beat, this glove offers a Level 5 cut resistance which is the highest standard currently recognized under EN388:2003. The glove is made from PYROHIDE® a top-grade, drum-dyed water, fire and chemical resistant analine cowhide grain leather outer which is sewn half pique. The cut resistance comes from a unique seamless knitted lining of KEVLAR® with glass-fibre made by Southcombe Brothers. The lining is plated with a Viloft® yarn offering active perspiration technology which wicks away moisture from the hand. The glove is accredited to EN388:2003 (Protective gloves against mechanical risks) and BS 7971 Part 7 (Slash Resistant Gloves).



TEST RESULTS

Test	Clause	Requirement	Result
pH Value	4.1	3.5 – 9.5	Pass
Chrome VI	4.1	≤ 2.0 mg/kg	Pass
Size & Dexterity	4.3	Pass	Pass
Ergonomics	4.4	Pass	Pass
Abrasion Resistance	4.5	Level 2	Level 3
Cut Resistance	4.6	Level 5	Level 5
Tear Resistance	4.7	Level 3	Level 4
Puncture Resistance	4.8	Level 2	Level 2
Burning Behaviour	4.8	Level 4	Level 4
Additional Properties			
Convective Heat	4.9	> 10 s	11.8 s - Pass
Radiant Heat	4.10	> 15 s	41.8 s - Pass
Heat Resistance - Lining	4.11	Pass	Pass
Chemical Resistance	4.13	Pass	Pass

MATERIALS

Outer shell: 100% Leather

Lining: 100% KEVLAR® with glass-fibre core

KEVLAR® only by DuPont

COLOUR

Black

SIZE RANGE

XS (7), S (8), M (9), L (10), XL (11), XXL (12)

CARE INSTRUCTIONS

Sponge clean only





Southcombe Brothers Ltd
Stoke-sub-Hamdon
Somerset TA14 6QD
UK

P: +44 (0) 1935 823567
F: +44 (0) 1935 822918
E: sales@southcombe.com
www.southcombe.co.uk

PYROHIDE® is a registered trademark of Southcombe Brothers Ltd, KEVLAR® is a registered trademark of Dupont